Applicant: Keiiti Ogura et al. Filed: October 1, 2001

: 7

Page

Attorney's Do

No.: 12732-077001 / US5246

## **REMARKS**

The amendments to the claims made herein are to correct minor grammatical errors and to place the application in better form for examination. No new matter is added.

Attached is a marked-up version of the changes being made by the current amendment.

Applicants ask that all claims be examined. Please apply any charges or credits to

Deposit Account No. 06-1050.

Respectfully submitted,

Date: October 1, 2001

John F. Hayden Reg. No. 37,640

Fish & Richardson P.C. 601 Thirteenth Street, NW Washington, DC 20005 Telephone: (202) 783-5070

Facsimile: (202) 783-2331

40070076.doc

Applicant: Keiiti Ogura et a Filed: October 1, 2001 Attorney's Do

No.: 12732-077001 / US5246

Page: 8

## Version with markings to show changes made

In the claims:

Claims 1, 3, 4, 6, 8-10, 12, 14, 15, 18, 20, 21, 23-25, 27, 30, 31, 33, 39, 40, 42, 47, 48 and 50-55 have been amended as follows:

1. (Amended) A light emitting device comprising[;]:

a substrate;

an EL element formed over [a] the substrate; and

an absorption film formed over the EL element;

wherein the EL element is interposed between the substrate and the absorption film.

- 3. (Amended) A device according to claim 1, wherein the absorption film comprises <u>an</u> alkaline-earth metal.
- 4. (Amended) A device according to claim 1, wherein the [inorganic] <u>absorption film</u> has <u>a thickness of 1 to 3 μm [thickness]</u>.
  - 6. (Amended) A light emitting device comprising[;]:
  - a first substrate;

an EL element formed over the first substrate;

an absorption film formed over the EL element; and

wherein the EL element is provided in a space surrounded by the first substrate, the sealant, and the sealing substrate.

- 8. (Amended) A device according to claim 6, wherein the absorption film comprises an alkaline-earth metal.
- 9. (Amended) A device according to claim 6, wherein the [inorganic] <u>absorption film</u> has <u>a thickness of</u> 1 to 3 μm [thickness].



Page : 9

10. (Amended) A device according to claim 6, wherein the sealant is not overlapped with the [inorganic] absorption film.

12. (Amended) A light emitting device comprising;

a substrate;

an EL element formed over the substrate, the EL element comprising an anode, an EL

layer, and a cathode; and

an absorption film formed over the cathode;

wherein the EL element is interposed between the substrate and the absorption film.

14. (Amended) A device according to claim 12, wherein the absorption film comprises an alkaline-earth metal.

15. (Amended) A device according to claim 12, wherein the [inorganic] absorption film has a thickness of 1 to 3  $\mu$ m [thickness].

18. (Amended) A light emitting device comprising[;]:

a substrate;

a TFT formed over the substrate[,];

an EL element electrically connected with the TFT; and

wherein the EL element is interposed between the substrate and the absorption  $\pi m$ .

20. (Amended) A device according to claim 18, wherein the absorption film comprises an alkaline-earth metal.

21. (Amended) A device according to claim 18, wherein the [inorganic] absorption film has a thickness of 1 to 3 µm [thickness].

Applicant: Keiiti Ogura et a Filed: October 1, 2001

: 10

Attorney's D

No.: 12732-077001 / US5246

Page

23. (Amended) A light emitting device comprising[;]:

a substrate;

an EL element formed over [a] the substrate; and

an inorganic hygroscopic film formed over the EL element for absorbing moisture;

wherein the EL element is enclosed by the substrate and the inorganic hygroscopic film.

24. (Amended) A device according to claim 23, wherein the inorganic hygroscopic film comprises <u>an</u> alkaline-earth metal.

25. (Amended) A device according to claim 23, wherein the inorganic <u>hygroscopic</u> film has <u>a thickness of 1 to 3 µm [thickness]</u>.

27. (Amended) A light emitting device comprising:

a first substrate;

an EL element comprising an organic light emitting layer formed over [a] the first substrate;

a barrier film covering the EL element;

an inorganic hygroscopic film formed over the barrier film wherein the barrier film is interposed between the inorganic hygroscopic film and the EL element.

- 30. (Amended) A device according to claim 27, wherein the inorganic hygroscopic film
- 31. (Amended) A device according to claim 27, wherein the inorganic <u>hygroscopic</u> film has <u>a thickness of 1 to 3 µm [thickness]</u>.
  - 33. (Amended) A light emitting device comprising:

a first substrate;

an EL element comprising an organic light emitting layer formed over [a] the first substrate;

Applicant: Keiiti Ogura et al. Filed: October 1, 2001

Attorney's Dd No.: 12732-077001 / US5246

Page : 11

a barrier film covering the EL element;

an inorganic hygroscopic film formed over the barrier film wherein the barrier film is interposed between the inorganic hygroscopic film and the EL element; and

a second substrate opposed to the first substrate with the EL element disposed therebetween wherein a space between the first and second substrates [are] is hermetically sealed by a sealant.

- 39. (Amended) A device according to claim 33, wherein the inorganic hygroscopic film comprises <u>an</u> alkaline-earth metal.
- 40. (Amended) A device according to claim 33, wherein the inorganic <u>hygroscopic</u> film has <u>a thickness of 1 to 3 μm [thickness]</u>.
  - 42. (Amended) A light emitting device comprising:
  - a first substrate;
- a plurality of switching elements formed over the first substrate, each of the switching elements comprising a thin film transistor;
- a plurality of EL elements formed over the first substrate and operationally connected to the switching elements, each of the EL elements comprising an organic light emitting layer;
  - a driver circuit comprising thin film transistors formed over the first substrate; an inorganic hygroscopic film formed over the plurality of EL elements and the driver
- a second substrate opposed to the first substrate with the EL element disposed therebetween wherein a space between the first and second substrates [are] is hermetically sealed by a sealant.
- 47. (Amended) A device according to claim 42, wherein the inorganic hygroscopic film comprises an alkaline-earth metal.

Applicant: Keiiti Ogura et a Filed: October 1, 2001

hygroscopic film is finished.

Attorney's D. No.: 12732-077001 / US5246

Page : 12

48. (Amended) A device according to claim 42, wherein the inorganic <u>hygroscopic</u> film has <u>a thickness of 1</u> to 3 µm [thickness].

50. (Amended) A method of manufacturing a light emitting device comprising the steps of:

providing a film formation apparatus;

forming an EL layer over a substrate in the film formation apparatus; and
forming an inorganic hygroscopic film over the EL layer in the film formation apparatus;
wherein the substrate is prevented from contacting an air outside of the film formation
apparatus after the formation of the EL layer and until the formation of the inorganic

- 51. (Amended) A method of manufacturing a light emitting device according to claim 50, wherein the inorganic hygroscopic film comprises <u>an</u> alkaline-earth metal.
- 52. (Amended) A method of manufacturing a light emitting device according to claim 50, wherein the inorganic <u>hygroscopic</u> film has <u>a thickness of 1 to 3 μm [thickness]</u>.
- 53. (Amended) A method of manufacturing a light emitting device comprising the steps of:

  providing a film formation apparatus having a plurality of chambers;

forming an inorganic hygroscopic film over the EL layer in [an] another chamber of the film formation apparatus;

and shamber of the film formation annaratus, and

wherein the steps from forming the EL layer to forming the inorganic hygroscopic film are performed without exposing the substrate to moisture and oxygen.

54. (Amended) A method of manufacturing a light emitting device according to claim[12] 53, wherein the inorganic hygroscopic film comprises an alkaline-earth metal.

Applicant: Keiiti Ogura et al. Filed: October 1, 2001 Attorney's Do No.: 12732-077001 / US5246

Page : 13

55. (Amended) A method of manufacturing a light emitting device according to claim[12] 53, wherein the inorganic <u>hygroscopic</u> film has <u>a thickness of</u> 1 to 3 μm [thickness].